



# Bart & Associates

## INDUSTRIAL EQUIPMENT & SUPPLIES

### I-CLEANER

#### ROTARY-SCREW COMPRESSOR CLEANER AND SYSTEM FLUSH

#### Applications:

I-Cleaner is a premium quality synthetic fluid designed to dissolve varnish and solubilize sludge from rotary-screw air compressors during operation. It can also be used as a system flush when changing-over from mineral to synthetic oils in order to reduce contamination due to oil carry-over. Regular use of I-Cleaner will help you get the most out of your synthetic oil and your compressor by removing varnish and reducing operating temperature.

#### **Typical Industrial Applications:**

- Rotary Screw Compressor
- Rotary Vane Compressor
- Centrifugal Compressor

#### Performance Benefits:

- Solubilizes and removes harmful varnish and "sludge"
- 100% synthetic
- Compatible with mineral oils as well as Ultrachem synthetic oils
- Contains no aromatic solvents or hazardous ingredients
- Contains additives so that it can be used as a lubricant for up to 500 hours
- High flash point
- Caution: May affect some paint finishes, plastics and seals
- USDA H-2 authorized

PROPERTY	TEST METHOD	I-Cleaner
ISO Grade	ASTM D2422	32
SAE Grade	SAE J-300	10
Viscosity @ 40°C,cSt	ASTM D445	37.1
Viscosity @ 100°C,cSt	ASTM D445	6.5
Viscosity Index	ASTM D2270	126
Flash Point, °C/°F	ASTM D92	204/400
Pour Point, °C/°F	ASTM D97	-45/-49
Copper Corrosion	ASTM D130	1b
Demulsibility	ASTM D1401	Excellent
Specific Gravity	ASTM D1298	0.94